

## **DEALSEAL N-300**

### **SECTION 1: IDENTIFICATION**

1.1 GHS Product identifier: DEALSEAL N-300

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses: Sealant

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

DEAL International Inc. 110 Halstead St. Rochester, NY 14610 Phone.: (585) 288-4444 Toll Free: (888) 880-3325 Fax: (585) 288-4578 www.DIIHQ.com

1.4 Emergency phone number: 911 Poison Control Center: +1 800-222-1222

## **SECTION 2: HAZARD(S) IDENTIFICATION**

## 2.1 Classification of the substance or mixture:

It is advised that, due to the inclusion of the active ingredient in an array, it is estimated that the dangers by inhalacion to the respiratory tract could be inhibited (this criterion prevails throughout the processing of the SDS)

#### NFPA:

Health Hazards: 2 Flammability Hazards: 0 Instability Hazards: 0

Special Hazards: Non-applicable

### 29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Skin Sens. 1: Sensitisation, skin, Category 1, H317

## 2.2 Label elements:

A label is not required for massive metals, alloys, mixes that contain polymers and mixes that contain elastomers if there is no hazard to human health due to inhalation, ingestion or contact with the skin, or to the aquatic environment, in the form in which it is marketed, even though they are classified as hazardous.

## NFPA:



### 29 CFR 1910.1200:

# Warning



### **Hazard statements:**

Skin Sens. 1: H317 - May cause an allergic skin reaction

## Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P272: Contaminated work clothing should not be allowed out of the workplace

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of soap and water

P333+P313: If skin irritation or rash occurs: Get medical advice/attention

P501: Dispose of contents and / or their container according to the separated collection system used in your municipality

## Substances that contribute to the classification

Butan-2-one O,O´,O´´-(methylsilylidyne)trioxime; N-(3-(trimethoxysilyl)propyl)ethylenediamine



### **DEALSEAL N-300**

## SECTION 2: HAZARD(S) IDENTIFICATION (continued)

### 2.3 Other hazards which do not result in classification:

Non-applicable

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substances:

Non-applicable

#### 3.2 Mixtures:

Chemical description: Based mixed polymers, dispersants and organic and inorganic compounds

#### Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. Exact percentage values for components are proprietary in accordance with 29 CFR 1910.1200(i). Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	Management Products	Hydrocarbons, C12-C16, iso-alkanes, cyclics, <2% aromatics Asp. Tox. 1: H304; Flam. Liq. 4: H227 - Danger	5 - <25 %
CAS:	22004 54 0	Butan-2-one O,O',O''-(methylsilylidyne)trioxime  Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	2,5 - <5 %
CAS:	2224 22 4	Butan-2-one O,O´,O´´-(vinylsilylidyne)trioxime  Eye Dam. 1: H318; Skin Sens. 1B: H317; STOT RE 2: H373 - Danger  \$\square\$ \tilde{\phi}\$ & \tilde{\phi}\$	0,1 - <1 %
CAS:	4700 24 2	N-(3-(trimethoxysilyl)propyl)ethylenediamine  Eye Dam. 1: H318; Skin Sens. 1: H317 - Danger	0,1 - <1 %

To obtain more information on the risk of the substances consult sections 8, 11, 12, 15 and 16.

## **SECTION 4: FIRST-AID MEASURES**

### 4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

## By inhalation:

The possibility of being breathed is practically nil, however, in the case of symptoms:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

### Bv skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

## 4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

## **SECTION 5: FIRE-FIGHTING MEASURES**

## 5.1 Suitable (and unsuitable) extinguishing media:



### **DEALSEAL N-300**

### SECTION 5: FIRE-FIGHTING MEASURES (continued)

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

### 5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

#### Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

#### 6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

### 6.3 Methods and materials for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

### 6.4 Reference to other sections:

See sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 41 °F
Maximum Temp.: 86 °F

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):



## **DEALSEAL N-300**

### SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

There are no occupational exposure limits for the substances contained in the product

### 8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

### B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. Use respirator in accordance with manufacturer's use limitations and OSHA standard 1910.134 (29CFR)

## C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

## D.- Ocular and facial protection

Pictogram	PPE	Remarks
Mandatory face protection	Face mask	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

## E.- Bodily protection

Pictogram	PPE	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration. Use foot protection in accordance with manufacturer's use limitations and OSHA standard 1910.136 (29CFR)

## F.- Additional emergency measures

It is not necessary to take additional emergency measures.

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2002	Eyewash stations	DIN 12 899 ISO 3864-1:2002



## **DEALSEAL N-300**

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F: Liquid
Appearance: Paste

Color: Not available
Odor: Not available

Volatility:

Boiling point at atmospheric pressure: 511 °F
Vapour pressure at 68 °F: 4 Pa

Vapour pressure at 122 ºF: 32 Pa (0 kPa)

Evaporation rate at 68 ºF: Non-applicable \*

**Product description:** 

Density at 68 °F: 990 kg/m³
Relative density at 68 °F: 0.99

Dynamic viscosity at 68 °F:

Kinematic viscosity at 68 °F:

Non-applicable \*

Non-applicable \*

Kinematic viscosity at 104 ºF: >20.5 cSt

Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 68 °F: Non-applicable \* Partition coefficient n-octanol/water 68 ºF: Non-applicable \* Solubility in water at 68 °F: Non-applicable \* Solubility properties: Non-applicable \* Non-applicable \* Decomposition temperature: Non-applicable \* Melting point/freezing point: Explosive properties: Non-applicable \*

Flammability:

Oxidising properties:

Flash Point: Non Flammable (>140 ºF)

Autoignition temperature: 455 °F

Lower flammability limit: Non-applicable \*
Upper flammability limit: Non-applicable \*

9.2 Other information:

Surface tension at 68 ºF:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity:

Non-applicable \*



### **DEALSEAL N-300**

## SECTION 10: STABILITY AND REACTIVITY (continued)

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

#### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Not applicable	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

## A.- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

## B- Inhalation (acute effect):

It is advised that, due to the inclusion of the active ingredient in an array, it is estimated that the dangers by inhalacion to the respiratory tract could be inhibited (this criterion prevails throughout the processing of the SDS)

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

## E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT)-time exposure:



## **DEALSEAL N-300**

## SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acut	Acute toxicity	
Butan-2-one O,O´,O´´-(methylsilylidyne)trioxime	LD50 oral	>5000 mg/kg	
CAS: 22984-54-9	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
Hydrocarbons, C12-C16, iso-alkanes, cyclics, <2% aromatics	LD50 oral	>5000 mg/kg	
CAS: Non-applicable	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L (4 h)	
Butan-2-one O,O´,O´´-{vinylsilylidyne}trioxime	LD50 oral	3519 mg/kg	Rat
CAS: 2224-33-1	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
N-(3-(trimethoxysilyI)propyI)ethylenediamine	LD50 oral	2413 mg/kg	Rat
CAS: 1760-24-3	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	

## **SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

## 12.1 Ecotoxicity (aquatic and terrestrial, where available):

Identification		Acute toxicity	Species	Genus
Butan-2-one O,O´,O´´-(vinylsilylidyne)trioxime	LC50	55000 mg/L (96 h)	QSAR	Fish
CAS: 2224-33-1	EC50	17168 mg/L (48 h)	QSAR	Fish
	EC50	1429 mg/L (96 h)	QSAR	Fish
N-(3-(trimethoxysilyl)propyl)ethylenediamine	LC50	597 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 1760-24-3	EC50	81 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	8.8 mg/L (72 h)	Selenastrum capricornutum	Algae

## 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Butan-2-one O,O´,O´´-(vinylsilylidyne)trioxime	BOD5	Non-applicable	Concentration	20 mg/L
CAS: 2224-33-1	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
N-(3-(trimethoxysilyl)propyl)ethylenediamine	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 1760-24-3	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	39 %

## 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Butan-2-one O,O´,O´´-(vinylsilylidyne)trioxime	BCF	1
CAS: 2224-33-1	Pow Log 0.6	
	Potential	Low

## 12.4 Mobility in soil:



## **DEALSEAL N-300**

## SECTION 12: ECOLOGICAL INFORMATION (continued)

Not available

### 12.5 Results of PBT and vPvB assessment:

Non-applicable

#### 12.6 Other adverse effects:

Not described

## **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Disposal methods:

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See epigraph 6.2.

## Regulations related to waste management:

Legislation related to waste management:

40 CFR Part 261- IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

### **SECTION 14: TRANSPORT INFORMATION**

This product is not regulated for transport.

## **SECTION 15: REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations specific for the product in question:

SARA Title III - Toxic Chemical Release Inventory Reporting (Section 313): Non-applicable

Hazardous substances release notification under CERCLA sections 102-103 (40 CFR Part 302): Non-applicable

California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986): Non-applicable

 $The Toxic Substances Control \ Act (TSCA): Butan-2-one \ O,O',O''-(methylsilylidyne) trioxime; Butan-2-one \ O,O',O''-(vinylsilylidyne) trioxime; N-(3-(trimethoxysilyl) propyl) ethylenediamine$ 

## Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

## Other legislation:

The Toxic Substances Control Act (TSCA)

SARA Title III - Community Right-to-Know Reporting Requirements (Sections 311-312)

SARA Title III - Toxic Chemical Release Inventory Reporting (Section 313)

Emergency Planning and Community Right-to-Know Act (EPCRA) Reportable Quantities

## **SECTION 16: OTHER INFORMATION**

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 – Safety data sheets

### Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction

## Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

- CONTINUED ON NEXT PAGE -

29 CFR 1910.1200:



## **DEALSEAL N-300**

### **SECTION 16: OTHER INFORMATION (continued)**

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 4: H227 - Combustible liquid Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction Skin Sens. 1B: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

#### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

## Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

#### Abbreviations and acronyms:

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol—water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current USA legislation, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.